



GlenSound



Includes:



GlenSound GS-GC5/USB

Commentary Mixer With USB Audio & Luci Live IP Codec

A 4 input commentator operated outside broadcast unit in the tradition of previous GlenSound ISDN units. This time, the audio I/O is via USB. The GS-GC5/USB includes LUCI live, the leading software IP solution. Using the USB audio link to a PC or notepad, IP calls can be established using several high quality codecs including AAC, AAC-HE and MP2

Key Points

Commentary Mixer

- 4 channel mixer with mic/line/48v phantom inputs
- Inputs have GlenSound Referee compressor/limiter system
- 4 x headphone outputs on 6.35mm jacks and 3.5mm jacks
- Headphone monitoring with 2 sources (MIX and CUE) with left/both/right switching
- Two line outputs on balanced XLR
- USB audio link to PC or notepad
- Includes USB to Ethernet converter to allow wired connection to network
- Internal Li-ion battery for 7 hours run time
- External 19v DC power

IP Codec

- GS-GC5/USB includes the full version of the Luci Live IP codec for PCs and notepads
- Codecs: MP2, AAC, AAC-HE, AAC-HEV2, G711, G722, ULCC
- 24 bit ULCC audio codec, 44.1 to 384 kHz sample rate
- RTP or UDP low-delay streaming, including return channel
- SC-RTP allows audio to be transmitted via multiple circuits simultaneously ie. wifi, LAN, 3G etc allowing for redundant links
- 1 way shoutcast/icecast streaming
- Record while broadcasting
- Play pre-recorded material while broadcasting
- N/ACIP compatible
- Sample rate from 44.1 to 384 kHz
- ASIO support on Windows

Preview Information
Shipping
November 2013



GlenSound

GlenSound 6 Brooks Place, Maidstone, Kent, ME14 1HE, UK.

Tel: +44 (0) 1622 753662

Email: sales@glenSound.co.uk

Web: www.glenSound.co.uk