




BEATRICE W1
 Wall Or Desk Mounting
 Beatrice Intercom Position

Highlights

Single Dante/AES67
 Intercom Position

AES67 Compliant

Flush Wall
 Mounting

Configurable Talk
 Button

PoE Powered

Internal & External
 Mic Connection

Overview

The Beatrice W1 is a single user interface for the Beatrice system, designed to mount flush on a wall or into a desk. It is a useful intercom position allowing two way communication to be possible at standing levels whilst mounted into walls, or at desk levels if mounted on a desk.




BEATRICE W1

Wall Or Desk Mounting
Beatrice Intercom Position

Connectivity for the Beatrice W1 is via a single Cat5/Cat6 cable which carries the audio to and from the unit, and also powers the unit via PoE, making installation very simple. The W1 has 1 input and 1 output to the Dante/AES67 network.



There is an internal loudspeaker to monitor the incoming audio which can be level adjusted. There is an internal microphone, and also an XLR for connecting an external goose neck microphone if required.

A single talk switch is available for routing the selected microphone onto the Dante/AES67 network. This can

be a momentary push to talk or a latching connection. A double tap of the talk key sends a call function to another Beatrice device. There is also an incoming call LED and a selectable audio alert for when a call signal is being received.



All settings are accessible via the configuration screen, including a party line mode, where the input is looped directly to the output.

A 4 input, 4 output version with 4 talk keys is also available, the Beatrice W4.

The name **Beatrice** was chosen for our intercom range as she was the love of Dante Alighieri:

'Dante had fallen in love with another, Beatrice Portinari (known as Bice), whom he first met when he was only nine.' Source Wikipedia.

We hope that you will also fall in love with Beatrice.